
PRODUCT INFORMATION

A PRODUCT OF VALVOLINE, A DIVISION OF ASHLAND INC. USA



VALVOLINE DURABLEND SAE 10W40 MOTOR OIL

Valvoline Durablend SAE 10W40 Motor Oil is formulated with a combination of high-tech synthetic and premium quality conventional base stocks combined with advanced additive technology. It helps engines maintain peak performance longer by providing improved wear control, deposit protection, volatility and low temperature flow characteristics versus conventional motor oils.

Valvoline Durablend SAE 10W40 Motor Oil provides protection under severe service conditions and meet the performance requirements of virtually all naturally aspirated, turbo charged and super charged gasoline passenger cars.

The Valvoline Durablend SAE 10W40 Motor Oil advantages

- **Breakdown Resistance:** Increases thermal and oxidation stability
- **Deposit Control:** Reduces formation of sludge and varnish deposits
- **Wear Protection:** Improves oil film strength and breakdown resistance
- **Cold start Properties:** Oil flows easily at low temperatures
- **Volatility:** Lowers oil vaporization and consumption at extreme conditions

Performance levels / Approvals	Typical Characteristics	
API SN / SL / CF	Kinematic Viscosity, cSt @ 100 ^o C	14.80
	Viscosity Index	154
	TBN, mg KOH/g (ASTM D-2896)	7.2
	Pour Point, ^o C, Max.	-30
	Flash Point, COC, ^o C	210
	CCS @ -25 ^o C, cP, Max.	6700

Available configurations: 6 x 1L case, 4 x 4L case

This information only applies to products manufactured in the following location(s) – Singapore

Effective date
28th April 2009

Authors Initials
SKM

Product code